

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



TCF30RN 30A Non-Inp Cube Fuse Bussmann Fuses

に影響だんと	
Catalog Number	TCF30RN
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series TCF Fuse, 30 A, 60 HZ, 50 HZ, Dual, CF, Black, Blade End, Time Delay, Class CF, 10 Sec At 500%, 300 Kaic At 600 V, 100 Kaic At 300 VDC, Glass Filled Pes, 35 MM Din Rail, Chassis, 600 V, 300 VDC
Weight per unit	
Product Category	
atures	
amperage rating	30 A
class	Class CF
connection	Blade End
dimensions	
element	Dual
interrupt rating	300 kAIC at 600 Vac100 kAIC at 300 Vdc
Material	Glass Filled PES
media	Voc
Response Time	10 S at 500%
Voltage Rating	600 Vac, 300 Vdc
scriptions	
Description	30A NON-INP CUBE FUSE
extra long description	BUSS TCF30RN CUBEFUSE, TCF 30A NON-
Features	The revolutionary BussmannTM series Low-PeakTM CUBEFuseTM delivers the smallest footprint compared to any Class CC, J or RK fuse solution — requiring up to 70 less space when combined with its unique fuse holder or UL 98 Listed Compact Circuit Protector switch. Freeing up space is powerful And the CUBEFuse does just that, while packing up to a 300 kA interrupting rating and enabling higher equipment short-circuit current rating (SCCR). Available from 1 to 400 amps.
Long Description	Eaton Bussmann series TCF fuse, 30 A, 60 Hz, 50 Hz, Dual, CF, Black, Blade end, Time delay, Class CF, 10 sec at 500%, 300 kAl at 600 V, 100 kAIC at 300 Vdc, Glass filled PES, 35 mm DIN rail, Chassis, 600 V, 300 Vdc
Product Type	Cubefuse, TCF 30A Non-Ind
Special Features	Finger Safe



ELLIOTT **E**LECTRIC **S**UPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	Eaton
GTIN	00051712220965
Manufacturers Part Number	TCF30RN
UPC	051712220965
Taxonomies, Classifications, and Ca	tegories
Category Description	Fuses & Fuse Accessories
Туре	FUSE
Packaging	
Carton	1
Package	12
Weight Per each	0.1
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Facility: Safety and Security
	SystemsDatacenters - Facilities: Power DistributionCommercial /
	Institutional Buildings / Structures - Critical PowerInd Facilities &
	Factories - Facility: Power Distribution and ControlStationary
	Machinery and Equipment Outside Factory - HVAC
Mounting	35 mm DIN Rail, Chassis
standard	CSA Certified, UL Listed, CE Marked, RoHS Compliant