## Specifications

Photo is representative

## Eaton TCF3RN

Eaton Bussmann Series Class CF fuse, TCF, time-delay, dual-element current limiting cube fuse, 3 A, non-idicating fuse, interrupting of 100 kA at 300 Vdc and 300 kA at 600 Vac

General specifications		
PRODUCT NAME	Eaton Bussmann series TCF fuse	
CATALOG NUMBER	TCF3RN	
UPC	051712220361	
PRODUCT LENGTH/DEPTH	1.88 in	
PRODUCT HEIGHT	1.75 in	
PRODUCT WIDTH	0.75 in	
PRODUCT WEIGHT	0.08 lb	
WARRANTY	Not Applicable	
COMPLIANCES	CE Marked	
CERTIFICATIONS	UL Listed CSA Certified	



## Electrical rating

AMPERAGE RATING	3 A
FREQUENCY RATING - MAX	60 Hz
FREQUENCY RATING - MIN	50 Hz
INTERRUPT RATING	300 kAIC at 600 Vac 100 kAIC at 300 Vdc
<b>RESPONSE TIME</b>	10 sec at 500%
VOLTAGE RATING	600 Vac, 300 Vdc

Physical details		
COLOR	Black	
FUSE TYPE	Class CF Time delay	
MATERIAL	Glass filled PES	
NUMBER OF ELEMENTS	Dual	
PACKAGING TYPE	Standard	

Low Voltage Branch Circuit Fuse Chapter
<u>Bussmann Full Line</u> <u>Catalog</u>
RoHS Search Tool
The Power of Space
<u>Bussmann series</u> <u>Fuseology</u>
<u>Bussmann series UL Class</u> <u>CF CUBEFuse data sheet</u> <u>no. 9000</u>

General information	
CLASS	Class CF
CONNECTION	Blade end
FUSE INDICATOR	Non-indicating
MOUNTING METHOD	Chassis 35 mm DIN rail
SPECIAL FEATURES	Finger safe
USED WITH	TCFH30N, CCP2-3-30CF

	ECT	
PRO	ECI	NAME:

**PROJECT NUMBER:** 

PREPARED BY:

DATE:



## Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

