

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Fea

TCF40 40A 600V Class J Fuse

Bussmann Fuses

Catalog Number	TCF40
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class CF Fuse, TCF, Time-Delay, Dual-Element Current Limiting Cube Fuse, 40 A, Indicating Fuse, Interrupting Rating Of 100 Ka At 300 VDC and 300 Ka At 600 Vac
Weight per unit	0.1800 (lbs/each)
Product Category	Tools & Testers
atures	
amperage rating	40
connection	Blade End
dimensions	2.1300 IN X 1.0000 IN X 1.9000 IN
element	Dual

element Dual Fuse Class CF

interrupt rating 100 kAIC at 300 Vdc300 kAIC at 600 Vac

Material Glass Filled PES

media Yes

Response Time 10 S at 500%

Voltage Rating 600 Vac, 300 Vdc

Dimensions and Weight

Size 2.13 In Length X 1.00 In Height

Descriptions

Description	40A 600V CLASS J FUSE
extra long description	BUSS TCF40 TIME DELAY CUBEFUSE 40A
Features	The revolutionary BussmannTM series Low-PeakTM CUBEFuseTM delivers the smallest footprint compared to any Class CC, J or RK fuse solution — requiring up to 70 less space when combined with its unique fuse holder or UL 98 Listed Compact Circuit Protector switch. Freeing up space is powerful. And the CUBEFuse does just that, while packing up to a 300 kA interrupting rating and enabling higher equipment short-circuit current rating (SCCR). Available from 1 to 400 amps.
Long Description	Eaton Bussmann Series Class CF fuse, TCF, time-delay, dual-element current limiting cube fuse, 40 A, indicating fuse, interrupting rating of 100 kA at 300 Vdc and 300 kA at 600 Vac
Product Type	Time Delay Cubefuse 40A Ind
Special Features	Finger Safe



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

	Inform	

Brand	Eaton
GTIN	00051712615051
Manufacturers Part Number	TCF40
UPC	051712615051

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Туре	FUSE

Packaging

okagirig	
Carton	12
Weight Per each	0.18

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security
	SystemsDatacenters - Facilities: Power DistributionCommercial /
	Institutional Buildings / Structures - Critical PowerInd Facilities &
	Factories - Facility: Power Distribution and ControlStationary
	Machinery and Equipment Outside Factory - HVAC
Mounting	35 mm DIN Rail, Chassis
standard	CSA Certified ,UL Listed,RoHS Compliant,CE Marked