



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## THHN400BK1000 THHN 400 STR Black 1000' *Southwire Company*



|                  |  |
|------------------|--|
| Catalog Number   | THHN400BK1000  |
| Manufacturer     | Southwire Company  |
| Description      | 600 Volts. Copper Conductor. Thermoplastic Insulation/Nylon Sheath, Heat, Moisture, Gasoline and Oil Resistant II. Rated THHN and THWN-2. Also Rated MTW. Simpull Technology For Easier Pulling. |
| Weight per unit  | 1.3 (lbs/ft)   |
| Product Category | THHN-T90-STR (Stranded)  |

### Features

|                      |                |
|----------------------|----------------|
| media                | Yes            |
| Number of Conductors | 1              |
| Tip Size             | 1000 ft. Spool |

### Dimensions and Weight

|        |      |
|--------|------|
| Length | 1000 |
|--------|------|

### Descriptions

|                        |  |
|------------------------|--|
| Description            | THHN 400 STR BLACK 1000'   |
| extra long description | SWC 20512001 THHN 400 Str Cu SIM Bk  |
| Long Description       | 600 Volts. Copper Conductor. Thermoplastic Insulation/Nylon Sheath, Heat, Moisture, Gasoline and Oil Resistant II. Rated THHN and THWN-2. Also rated MTW. SIMpull Technology for Easier Pulling. |
| Special Features       | No Lube  |

### Manufacturer Information

|       |                |
|-------|----------------|
| Brand | Copper         |
| GTIN  | 00032886234361 |
| UPC   | 032886234361   |

### Taxonomies, Classifications, and Categories

|                      |               |
|----------------------|---------------|
| Category Description | BUILDING WIRE |
| Type                 | THHN-2        |

### Availability

|             |      |
|-------------|------|
| minimum qty | 1000 |
|-------------|------|

### Packaging

|                 |       |
|-----------------|-------|
| Carton          | 1000  |
| Weight Per foot | 1.334 |