

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



TN228 BLTF 3/8" Twirl Nut (Cone Nut) Cooper B-Line/Cable Tray

Catalog Number	TN228		
Manufacturer	Cooper B-Line/Cable Tray		
Description	Twirl Nut, Steel, Zinc Plated, 3/8 In Diameter, 0.09 LB		
Weight per unit	0.0900 (lbs/each)		
Product Category	Screws, Nuts, Bolts, Washers		

Features

1.3750 IN X 0.8500 IN X 0.3750 IN dimensions

Dimensions and Weight

Size 3/8 In-16 TPI

Descriptions

Also Known As	Boingie Nut		
	Spring Nut (Strut)		
Description	BLTF 3/8" TWIRL NUT (CONE NUT)		
extra long description	B-LINE TN228ZN TWIRL-NUT, 3/8"-16 T		
Features	For a complete strut offering, Eaton offers a full line of B-Line series channel nuts, u-bolts and all threaded rod that are essential to any strut assembly. This line also includes a number of innovative solutions that help installers save time and materials on the job-site.		
Special Features	Without Spring, Thickness 3/8 In, Weight 9.3 Lb per 100		

Manufacturer Information

Brand	Eaton
GTIN	00781011401733
UPC	781011401733

Taxonomies, Classifications, and Categories

Category Description	SPRING NUTS & TWIRL NUTS
Туре	Nut

Availability

Status	Inac	tive
--------	------	------

Packaging

Carton	1	
Package	100	
Weight Per each		

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-56-7941

Fax: 936-560-4685

Uses, Certifications, and Standards

Application

UtilityOther IT and Datacom - Other InfrastructuresGeneration - Renewable Energy - Alternative EnergyDatacenters - IT Space:
Enterprise / Server Room / Network ClosetResidential Bldgs & Facilities - Residential Bldgs & Facilities - OtherGeneration - Conventional Energy - Conventional EnergyCommercial / Institutional Buildings / Structures - Commercial / Institutional Buildings / Structures - OtherInd Facilities & Factories - Industrial Facilities/Factories - OtherDatacenters - Datacenters -

OtherCommercial

standard Not Applicable