

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





TPC350 3-1/2" Three Piece Coupling Appleton/Oz Gedney

| Catalog Number | TPC350 |
|------------------|---|
| Manufacturer | Appleton/Oz Gedney |
| Description | Conduit Hardware, Couplings, Armored Cable, Type: Threaded, |
| | Trade Size: 3 1/2 Inch, For Use With: Rigid or Imc, Material: |
| | Malleable Iron |
| Weight per unit | 6.2 (lbs/each) |
| Product Category | Rigid Conduit Fittings - Steel |

Features

connection Threaded Threaded Coupling Connector Type

Material, Color, and Finish

Metallic Color

Dimensions and Weight

Length 2.54

Descriptions

| Description | 3-1/2" THREE PIECE COUPLING |
|------------------------|--|
| extra long description | EGS TPC-350 3-1/2 IN 3 PIECE CPLG |
| Long Description | Conduit Hardware, Couplings, Armored Cable, Type: Threaded, Trade Size: 3 1/2 Inch, For Use With: Rigid or IMC, Material: Malleable Iron |
| Product Type | 3-1/2 In 3 Piece CPLG |
| Special Features | 3-1/2 IN Trade Size Three Piece Coupling, For Use With Rigid and IMC Conduit |

Manufacturer Information

| Brand | Appleton |
|---------------------------|----------------|
| GTIN | 00687855404759 |
| Manufacturers Part Number | TPC-350 |
| UPC | 687855404759 |

Taxonomies, Classifications, and Categories

| Category Description | Watertight Hub, 3-PIECE COUPLINGS, THREADLESS COUPLINGS |
|----------------------|---|
| | AND THREADLESS CONNECTOR |
| Туре | Three Piece Coupling |
| Trade Size | |
| Trade Size | 3.5 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| Packaging | |
|-------------------------------------|---|
| Carton | 5 |
| Weight Per each | 6.2 |
| Uses, Certifications, and Standards | |
| Application | Provides threaded coupling between lengths of conduit and IMC |
| | elbows, where neither can be rotated |
| standard | NEMA: FB-1;UL Listed: E163167;UL Standard: 514B |