

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



TR225R 250V RK5 TD Fuse

Mersen Fuses

Catalog Number	TR225R		
Manufacturer	Mersen Fuses		
Description	Fuse TR-R - Class RK5 - Time-Delay 250VAC 250VDC 225A Blade Tri-Onic®		
Weight per unit	1.8 (lbs/each)		
Product Category	Current Limiting		
Features			
AC Voltage Rating	250		
amperage rating	225		
class	Class RK5		
connection	Blade		
interrupt rating	200		
Voltage Rating	250		
Material, Color, and Finish			
Body Material	PolyTube		
Dimensions and Weight			
Size	8.63 x 2.06		



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Laccrintion	c
Description :	
- 0001 .p t.o	•
•	

Marrier TD00FD F and TD D Olary DVF	
Mersen TR225R Fuse TR-R - Class RK5	
Tri-Onic TR-R current-limiting time-delay fuses are engineered for overcurrent protection of motors, transformers, service entrance equipment, feeders and branch-circuits. The time-delay characteristics of the TR-R safely handle harmless starting currents and inrush currents associated with today's motors and transformers.	
Fuse TR-R - Class RK5 - Time-Delay 250VAC 250VDC 225A Blade Tri-Onic®	
Fuse TR-R - Class RK5 - Time-Delay 250VAC 250VDC 225A Blade	
250V 225A 8 5/8x2 1/10 TD	
Time-delay Current-limiting AC & DC rated Optional solid state SmartSpot blown fuse indicator Time-delay for motor start-ups and transformer inrush currents without nuisance opening Current-limiting for low peak let-thru current Rejection-style design prevents replacement errors (when used with recommended fuse blocks) Easy-to-read label for quick brand recognition and replacement Metal-embossed date and catalog number for traceability and lasting identification Fiberglass body provides dimensional stabili	

Mar

Type

Brand	Mersen
GTIN	00782001748111
Manufacturers Part Number	TR225R
UPC	782001748111

Taxonomies, Classifications, and Categories

Packaging		
Carton	1	
Weight Per each	1.8	

CLASS RK5

Uses, Certifications, and Standards

Application	Motor circuits Mains Feeders Branch circuits Transformers	
	Service entrance equipment General-purpose equipment	
Mounting	Clip	
standard	UL listed to standard 248-12 File E2137 CSA certified to standard	
	C22.2 no. 248.12 DC listed to UL standard 248 TRS only	