

EMT Couplings, 90° Connectors and Caps/Heads

COMMERCIAL PRODUCTS: EMT FITTINGS

| | Catalog Number | Trade Size (Inches) | | Dimensions in Inches/Millimeters | | | Weight Lbs./Kgs. Per 100 | |
|--|----------------|---------------------|--|----------------------------------|----------------|----------------|--------------------------|---|
| | | | | A | B | C | | |
| Combination Coupling – EMT to Flexible Metal Conduit – Zinc Diecast | | | | | | | | |
|  | TW38-50DC † | 1/2 | — | 1.28/ 32.5 | 1.25/ 31.8 | 0.94/ 23.9 | 7.50/ 3.40 |  |
| Combination Coupling – EMT to Flexible Metal Conduit – Malleable Body/Nut | | | | | | | | |
|  | TWCC38-50 † | 1/2 | — | 0.84/ 21.3 | 0.63/ 16.0 | 1.06/ 26.9 | 12.00/ 5.44 |  |
| | TWCC-50 | 1/2 | — | 0.88/ 22.4 | 0.63/ 16.0 | 1.06/ 26.9 | 14.50/ 6.58 | |
| | TWCC-75 | 3/4 | — | 1.06/ 26.9 | 0.66/ 16.8 | 1.31/ 33.3 | 25.00/ 11.34 | |
| | TWCC-100 | 1 | — | 1.19/ 30.2 | 0.84/ 21.3 | 1.88/ 47.8 | 61.00/ 27.67 | |
| Gland Compression 90° Long Connectors – Concrete Tight – Malleable/Steel Nut | | | | | | | | |
|  | TWLL-50L | 1/2 | — | 1.88/ 47.8 | 2.06/ 52.3 | 0.59/ 15.0 | 32.00/ 14.51 |  |
| | TWLL-75L | 3/4 | — | 2.19/ 55.6 | 2.44/ 62.0 | 0.44/ 11.2 | 50.00/ 22.68 | |
| | TWLL-100L | 1 | — | 2.59/ 65.8 | 3.00/ 76.2 | 0.44/ 11.2 | 105.00/ 47.63 | |
| | TWLL-125L | 1-1/4 | — | 2.81/ 71.4 | 3.31/ 84.1 | 0.56/ 14.2 | 136.00/ 61.69 | |
| Gland Compression 90° Short Connectors – Concrete Tight – Malleable/Steel Nut | | | | | | | | |
|  | TWL-50L | 1/2 | — | 1.22/ 31.0 | 1.31/ 33.3 | 0.41/ 10.4 | 20.00/ 9.07 |  |
| | TWL-75L | 3/4 | — | 1.31/ 33.3 | 1.44/ 36.6 | 0.44/ 11.2 | 30.00/ 13.61 | |
| | TWL-100L | 1 | — | 1.63/ 41.4 | 1.56/ 39.6 | 0.44/ 11.2 | 53.00/ 24.04 | |
| Set Screw Entrance Caps – Exclusive “Snap-On” Cover – Malleable Iron | | | | | | | | |
|  | EF-125 | 1-1/4 | (3) 5/8” and (2) 13/32” | 4.31/ 109.5 | 2.88/ 73.2 | 3.63/ 92.2 | 64.00/ 29.03 |  |
| | EF-150 | 1-1/2 | (3) 25/32”, (2) 9/16” and (1) 3/8” | 5.00/ 127.0 | 3.31/ 84.1 | 4.34/ 110.2 | 93.00/ 42.18 | |
| | EF-200 | 2 | (3) 1”, (2) 3/4 and (3) 17/32” | 6.34/ 161.0 | 4.50/ 114.3 | 5.56/ 141.2 | 183.00/ 83.01 | |
| | EF-250 | 2-1/2 | (3) 7/8”, (1) 1” and (3) 1-5/16” | 9.00/ 228.6 | 6.25/ 158.8 | 7.75/ 196.9 | 350.00/ 158.76 | |

† Not UL Listed

EMT Couplings, 90° Connectors and Caps/Heads

COMMERCIAL PRODUCTS: EMT FITTINGS

| | Catalog Number | Trade Size (Inches) | | Dimensions in Inches/Millimeters | | | Weight Lbs./Kgs. Per 100 | |
|--|----------------|---------------------|--|----------------------------------|----------------|----------------|--------------------------|---|
| | | | | A | B | C | | |
| Combination Coupling – EMT to Flexible Metal Conduit – Zinc Diecast | | | | | | | | |
|  | TW38-50DC † | 1/2 | — | 1.28/ 32.5 | 1.25/ 31.8 | 0.94/ 23.9 | 7.50/ 3.40 |  |
| Combination Coupling – EMT to Flexible Metal Conduit – Malleable Body/Nut | | | | | | | | |
|  | TWCC38-50 † | 1/2 | — | 0.84/ 21.3 | 0.63/ 16.0 | 1.06/ 26.9 | 12.00/ 5.44 |  |
| | TWCC-50 | 1/2 | — | 0.88/ 22.4 | 0.63/ 16.0 | 1.06/ 26.9 | 14.50/ 6.58 | |
| | TWCC-75 | 3/4 | — | 1.06/ 26.9 | 0.66/ 16.8 | 1.31/ 33.3 | 25.00/ 11.34 | |
| | TWCC-100 | 1 | — | 1.19/ 30.2 | 0.84/ 21.3 | 1.88/ 47.8 | 61.00/ 27.67 | |
| Gland Compression 90° Long Connectors – Concrete Tight – Malleable/Steel Nut | | | | | | | | |
|  | TWLL-50L | 1/2 | — | 1.88/ 47.8 | 2.06/ 52.3 | 0.59/ 15.0 | 32.00/ 14.51 |  |
| | TWLL-75L | 3/4 | — | 2.19/ 55.6 | 2.44/ 62.0 | 0.44/ 11.2 | 50.00/ 22.68 | |
| | TWLL-100L | 1 | — | 2.59/ 65.8 | 3.00/ 76.2 | 0.44/ 11.2 | 105.00/ 47.63 | |
| | TWLL-125L | 1-1/4 | — | 2.81/ 71.4 | 3.31/ 84.1 | 0.56/ 14.2 | 136.00/ 61.69 | |
| Gland Compression 90° Short Connectors – Concrete Tight – Malleable/Steel Nut | | | | | | | | |
|  | TWL-50L | 1/2 | — | 1.22/ 31.0 | 1.31/ 33.3 | 0.41/ 10.4 | 20.00/ 9.07 |  |
| | TWL-75L | 3/4 | — | 1.31/ 33.3 | 1.44/ 36.6 | 0.44/ 11.2 | 30.00/ 13.61 | |
| | TWL-100L | 1 | — | 1.63/ 41.4 | 1.56/ 39.6 | 0.44/ 11.2 | 53.00/ 24.04 | |
| Set Screw Entrance Caps – Exclusive “Snap-On” Cover – Malleable Iron | | | | | | | | |
|  | EF-125 | 1-1/4 | (3) 5/8” and (2) 13/32” | 4.31/ 109.5 | 2.88/ 73.2 | 3.63/ 92.2 | 64.00/ 29.03 |  |
| | EF-150 | 1-1/2 | (3) 25/32”, (2) 9/16” and (1) 3/8” | 5.00/ 127.0 | 3.31/ 84.1 | 4.34/ 110.2 | 93.00/ 42.18 | |
| | EF-200 | 2 | (3) 1”, (2) 3/4 and (3) 17/32” | 6.34/ 161.0 | 4.50/ 114.3 | 5.56/ 141.2 | 183.00/ 83.01 | |
| | EF-250 | 2-1/2 | (3) 7/8”, (1) 1” and (3) 1-5/16” | 9.00/ 228.6 | 6.25/ 158.8 | 7.75/ 196.9 | 350.00/ 158.76 | |

† Not UL Listed