

EMT Combination Couplings and Connectors

Application
- Couplings are used to join lengths of steel EMT to various raceway systems.
- Connectors are used to secure and terminate steel EMT to knockouts and concreate tight box.

Features
- Compact design.
- No locknut required on the two piece connectors.
- Quick installations.

Material
- Steel, zinc diecast or malleable iron

Certifications and Compliances
- UL Standard: 514B
- UL Listed: E14895 (TWLL), E14814 (TWCC)
- NEMA: FB-1

	Trade Size (Inches)	Catalog Number	Dimensions in Inches/Millimeters A	B	C	Weight Lbs./ Kgs. Per 100	
Combination Couplings — EMT to Rigid Metal Conduit — Steel							
	1/2	**TWR-50**	0.69/17.5	0.50/12.7	1.00/25.4	10.00/4.54	
	3/4	**TWR-75**	0.69/17.5	0.53/13.5	1.28/32.5	15.00/6.80	
	1	**TWR-100**	0.88/22.4	0.53/13.5	1.59/40.4	17.00/7.71	
	1-1/4	**TWR-125**	0.97/24.6	0.84/21.3	1.94/49.3	40.00/18.14	
Connectors — Two Piece — Concrete Tight — Steel							
	1/2	**92T050**	0.31/7.9	0.34/8.6	1.06/26.9	6.00/2.72	
	3/4	**92T075**	0.31/7.9	0.44/11.2	1.28/32.5	8.80/3.99	
	1	**92T100**	0.34/8.6	0.41/10.4	1.63/41.4	13.00/5.90	

© September 2010



EMT Combination Couplings and Connectors

Application
- Couplings are used to join lengths of steel EMT to various raceway systems.
- Connectors are used to secure and terminate steel EMT to knockouts and concreate tight box.

Features
- Compact design.
- No locknut required on the two piece connectors.
- Quick installations.

Material
- Steel, zinc diecast or malleable iron

Certifications and Compliances
- UL Standard: 514B
- UL Listed: E14895 (TWLL), E14814 (TWCC)
- NEMA: FB-1

	Trade Size (Inches)	Catalog Number	Dimensions in Inches/Millimeters A	B	C	Weight Lbs./ Kgs. Per 100	
Combination Couplings — EMT to Rigid Metal Conduit — Steel							
	1/2	**TWR-50**	0.69/17.5	0.50/12.7	1.00/25.4	10.00/4.54	
	3/4	**TWR-75**	0.69/17.5	0.53/13.5	1.28/32.5	15.00/6.80	
	1	**TWR-100**	0.88/22.4	0.53/13.5	1.59/40.4	17.00/7.71	
	1-1/4	**TWR-125**	0.97/24.6	0.84/21.3	1.94/49.3	40.00/18.14	
Connectors — Two Piece — Concrete Tight — Steel							
	1/2	**92T050**	0.31/7.9	0.34/8.6	1.06/26.9	6.00/2.72	
	3/4	**92T075**	0.31/7.9	0.44/11.2	1.28/32.5	8.80/3.99	
	1	**92T100**	0.34/8.6	0.41/10.4	1.63/41.4	13.00/5.90	

© September 2010