

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

TY525M 7.31" "Ty-Rap" Cable Tie Abb Installation Products, Inc

TY525M
Abb Installation Products, Inc
Cable Tie, Natural Polyamide (Nylon 6.6) For Temperatures Up to
85 Degrees Celsius (185 F) For Indoor Applications,
UI/En/CSA62275 Type 2/21S Rated For Ah-2 Plenum and As A
Flexible Cable and Conduit Support, Length Of 185.67MM (7.31
Inches), Width Of 4.9MM (0.19 Inches), Thickness Of 1.09MM
(0.043 Inches), Tensile Strength Rating Of 222 Newtons (50
Pounds)
0.0040 (lbs/each)
Cable Ties & Wraps
0.12 to 1.89 in , 3 to 48 mm
Nylon/Polyamide 6.6
50 pounds , 222 newtons
lvory
7.2 in , 183 mm
0.05 in , 1.3 mm
0.19 in , 4.9 mm
7.31" "TY-RAP" CABLE TIE
ABB TY525M CABLE TIE 50LB 7 NAT NYL
Cable Tie, Natural Polyamide (Nylon 6.6) for Temperatures up to
85 Degrees Celsius (185 F) for Indoor Applications,
UL/EN/CSA62275 Type 2/21S Rated for AH-2 Plenum and as a
Flexible Cable and Conduit Support, Length of 185.67mm (7.31
Inches), Width of 4.9mm (0.19 Inches), Thickness of 1.09mm
(0.043 Inches), Tensile Strength Rating of 222 Newtons (50
Pounds)
Cable Tie 50LB 7 Nat Nylon 2-PC Di
Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless
steel locking device insures both maximum strength and the right
tightness every time



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

и		_		1		_ 1				.					_
ľ	۱ <i>۱</i>	12	n		-	СТ		·Δr	ın	TO	۱rr	ทว	TI	n	7
	v			u	а	L.I	uı	C-1	'In	H.V.	,, ,	па		u	

Brand	Ty-Rap
GTIN	00786210805092
Manufacturers Part Number	TY525M
UPC	786210805092

Taxonomies, Classifications, and Categories

Category Description	Screws, Bolts, Staples, Jack Chains, Washers & TY-Raps
Type	HIGH PERFORMANCE

Packaging

Carton	100
Package	1000
Weight Per each	0.004

Uses, Certifications, and Standards

-	-		
standard		E49405	