

R

## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| <b>TY526ME</b> | 11" "T | y-Rap" | Cable | Tie |
|----------------|--------|--------|-------|-----|
|                |        |        |       |     |

Abb Installation Products, Inc

| Catalog Number                     | TY526ME   |  |  |
|------------------------------------|---|--|--|
| Manufacturer                       | Abb Installation Products, Inc  |  |  |
| Description                        | Cable Tie, Standard Style, Nylon/Polyamide 6.6 Material, Ivory,<br>11.08 In Length, 0.08 In (Minimum);3.0 In (Maximum) Bundle<br>Diameter, 0.14 In Width, 0.05 In Thickness, 30 LB/135 N Tensile<br>Strength + 195 °C Operating Temperature - 0.0025 LB |  |  |
| Weight per unit                    | Strength, +185 °F Operating Temperature, 0.0025 LB<br>0.0025 (lbs/each)   |  |  |
| Product Category                   |   |  |  |
| Descriptions                       |   |  |  |
| Description                        | 11" "TY-RAP" CABLE TIE  |  |  |
| extra long description             | ABB TY526M CBL TIE 30LB 11.10 PO NA   |  |  |
| Special Features                   | Low profile head is designed to prevent snags on uneven surfac<br>and easier to pull through bulkheads. Non-magnetic stainless<br>steel locking device insures both maximum strength and the rig<br>tightness every time                                |  |  |
| Manufacturer Information           |   |  |  |
| Brand                              | Ty-Rap  |  |  |
| GTIN                               | 00786210825496  |  |  |
| UPC                                | 786210825496  |  |  |
| Taxonomies, Classifications, and C | Categories  |  |  |
| Category Description               | •   |  |  |
| Туре                               | HIGH PERFORMANCE  |  |  |
| Availability                       |   |  |  |
| minimum qty                        | 100   |  |  |
| Status                             | Inactive  |  |  |
| Packaging                          |   |  |  |
| Carton                             | 1000  |  |  |
| Package                            | 10000   |  |  |
| Weight Per each                    | 0.0025  |  |  |
| Uses, Certifications, and Standard | S   |  |  |
| standard                           | UL E49405 / UL E49405   |  |  |