

Category Description

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

UL12500 1/2" Ua Sealtite Conduit, Bonded UI 500' *Southwire Company*

Catalog Number	UL12500	
Manufacturer	Southwire Company	
Description	TITAN2 Type UI LFMC Is Manufactured With A Spiral Wound S Of Heavy Gauge Corrosion-Resistant Hot-Dipped Galvanized Steel. For 3/8" Through 1-1/4" Trade Sizes The Core Is Constructed With A Square Locked Steel Strip With An Integra Copperbonding Strip Enclosed Within The Steel Convolutions. 1-1/2" Through 4" Trade Sizes The Core Is Constructed With A Fully Interlocked Steel Strip. A Rugged Flame Retardant Flexible PVC Jacket Is Extruded Over The Steel Core. The Grey Jacket Resists Oils Mild	
Weight per unit	0.3100 (lbs/ft)	
Product Category	Conduit & Raceways	
eatures		
outside diameter	830	
imensions and Weight		
Length	500	
escriptions		
Description	1/2" UA SEALTITE CONDUIT, BONDED UL 500'	
extra long description	SWC 55082605 Titan2 Type UL Liquidt	
Long Description	Titan2 Type UL LFMC is manufactured with a spiral wound strip of heavy gauge corrosion-resistant hot-dipped galvanized stee For 3/8" through 1-1/4" trade sizes the core is constructed with a square locked steel strip with an integral copperbonding strip enclosed within the steel convolutions. For 1-1/2" through 4" trade sizes the core is constructed with a fully interlocked steel strip. A rugged flame retardant flexible PVC jacket is extruded over the steel core. The grey jacket resists oils mild	
Product Type	TITAN2 Type UI Liquidtight Flexible Metal Conduit	
lanufacturer Information		
Brand	Flexible Conduit	
GTIN	00032886052613	
Manufacturers Part Number	55082605	
UPC	032886052613	

Liquid Tight



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

rade Size		
Trade Size	1/2	
Packaging		
Carton	500	
Weight Per foot	0.31	