



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



UNF200NRA 2" Alu Female Union

Appleton/Oz Gedney

Catalog Number	UNF200NRA
Manufacturer	Appleton/Oz Gedney
Description	Appleton UNF200NR-A Unilets Unf Union, Trade Size: 2 In, Outside Diameter: 3.72 In, Length: 2.31 In, Flexibility: Rigid and Imc, Material: Copperfree (4/10 Of 1 PCT Maximum) Aluminum, Connection: Female Threaded, Finish: Natural, Standard: UI 886 (1203),
Weight per unit	0.8500 (lbs/each)
Product Category	Boxes & Covers

Features

connection	Female Threaded
outside diameter	3.72

Dimensions and Weight

Length	2.31
--------	------

Descriptions

Description	2" ALU FEMALE UNION
extra long description	APP UNF200NR-A 2 UNION CONNECTOR TY
Long Description	Appleton UNF200NR-A UNILETS UNF Union, Trade Size: 2 IN, Outside Diameter: 3.72 IN, Length: 2.31 IN, Flexibility: Rigid And IMC, Material: Copperfree (4/10 Of 1 PCT Maximum) Aluminum, Connection: Female Threaded, Finish: Natural, Standard: UL 886 (1203),
Product Type	2 Union Connector Type Unf
Special Features	Accurately tapped, tapered threads for tight, rigid joints and ground continuity;Concentric ring interlocked design sizes makes possible smaller diameter, allowing use in tighter spaces;Explosionproof, dust-ignitionproof;Smooth, rounded integral bushing in each hub protects conductor insulation;UNF unions are used for joining conduit and connecting conduit to enclosures, Facilitates modifications, permits removal of enclosures without turning or removal of conduit

Manufacturer Information

Brand	Appleton
GTIN	00781381257718
Manufacturers Part Number	UNF200NR-A
UPC	781381257718



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	HAZARDOUS LOCATION FITTINGS
Type	UNF Union

Trade Size

Trade Size	2
------------	---

Packaging

Carton	1
Weight Per each	0.85

Uses, Certifications, and Standards

Application standard	For Connecting Conduit To Conduit and Class II, CSA C22.2 No. 25, C22.2 No. 30, CSA 065181 Certified;Class II, Groups E, F, G;UL 886 (1203), UL File Number E10444, UL Listed for Class I, Groups B, C, d
-------------------------	--