

## ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





Type

## **UNY200NR 2" Male Union** *Appleton/Oz Gedney*

Catalog Number	UNY200NR
Manufacturer	Appleton/Oz Gedney
Description	Unilets Uny Union, Trade Size: 2 In, Outside Diameter: 3.72 In, Length: 3.63 In, Flexibility: Rigid and Imc, Material: Malleable Iron, Connection: Male Threaded X Female Threaded, Finish: Triple-Coat (Zinc Electroplate, Chromate and Epox
Weight per unit	·
Product Category	
eatures	
connection	Male Threaded X Female Threaded
outside diameter	3.72
mensions and Weight	
Length	3.63
escriptions	
Description	2" MALE UNION
extra long description	APP UNY200NR 2 UNION CONNECTOR TYPE
Long Description	UNILETS UNY Union, Trade Size: 2 IN, Outside Diameter: 3.72 IN Length: 3.63 IN, Flexibility: Rigid And IMC, Material: Malleable Iron, Connection: Male Threaded X Female Threaded, Finish: Triple-Coat (Zinc Electroplate, Chromate And Epox
Product Type	2 Union Connector Type Uny
Special Features	Accurately tapped, tapered threads for tight, rigid joints and ground continuity; Concentric ring interlocked design sizes make possible smaller diameter, allowing use in tighter spaces; Explosionproof, dust-ignitionproof; Smooth, rounded integral bushing in each hub protects conductor insulation; UNY unions are used for joining conduit and connecting conduit to enclosures, Facilitates modifications, permits removal of enclosures without turning or removal of conduit; With removable male nipple
anufacturer Information	
Brand	Appleton
GTIN	00781381257770
Manufacturers Part Number	UNY200NR
UPC	781381257770

Category Description HAZARDOUS LOCATION FITTINGS

**UNY Union** 



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Trade Size	
Trade Size	2
Packaging	
Carton	10
Weight Per each	2.7
Uses, Certifications, and Stand	dards
Application	For Connecting Conduit To Enclosure
standard	and Class II, CSA C22.2 No. 25, C22.2 No. 30, CSA 065181
	Certified; Class II, Groups E, F, G; UL 886 (1203), UL File Number
	E10444, UL Listed for Class I, Groups B, C, d