

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



V48M28T45EE 45KVA 3PH 480V TP-1 Delta Transformer Eaton Corp

Catalog Number	V48M28T45EE
Manufacturer	Eaton Corp
Description	Eaton General Purpose Ventilated Transformer, DT-3 (3-Phase),
	PV 480V, Taps: 2 At +2.5% /4 At -2.5%, SV 208Y/120V, 150°C Rise
	W/ 200°C Insulation Systeam, 45 Kva, Ee
Weight per unit	310.0 (lbs/each)
Product Category	Three Phase Energy Efficient D
Features	
dimensions	16.5000 IN X 23.0000 IN X 32.0200 IN
media	Yes
Number of Phases	
Tap Size	2 at +2.5% FCAN, 4 at -2.5% FCBN
Descriptions	
Description	45KVA 3PH 480V TP-1 DELTA TRANSFORMER
extra long description	ETN V48M28T45EE 45KVA DT-3 TX 3PH 4
Features	Eaton types DS-3 (single-phase) and DT-3 (three-phase) general
	purpose ventilated dry-type transformers are two-winding,
	self-cooled, and available in a wide variety of primary and
	secondary voltage combinations. General purpose transformers
	are designed for continuous operation at rated kVA. They are
	designed, manufactured and tested in accordance with all of the
	latest applicable ANSI, NEMA and IEEE standards.
Long Description	Eaton General purpose ventilated transformer, DT-3 (3-phase),
	PV 480V, Taps: 2 at +2.5% /4 at -2.5%, SV 208Y/120V, 150°C rise
	w/ 200°C insulation systeam, 45 kVA, EE
Product Type	45KVA DT-3 TX 3PH 480D-208Y/120V 150C
Manufacturer Information	
Brand	Eaton
GTIN	00786680019357
Manufacturers Part Number	V48M28T45EE
UPC	786680019357
Faxonomies, Classifications, and (Categories
Category Description	
Туре	Ventilated transformer
Availability	
Status	Inactive



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Weight Per each	310
Uses, Certifications, and Standards	
Application	Commercial / Institutional Buildings / Structures - Safety and
	Security Systems
standard	UL Listed, NEMA TP-1 Compliant