

Vulite®

# 4" IC NEW CONSTRUCTION HOUSING

INCANDESCENT LAMPS

V4IC W

Project: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Location: \_\_\_\_\_

Contact/Phone: \_\_\_\_\_

## PRODUCT DESCRIPTION

IC Air-Loc® Housing with all 4" trims complies with IECC, Washington State and other state Energy Codes • Double wall construction • Energy efficient, sealed inner housing does not require separate ALG gasket • Air-Loc housing stops infiltration and exfiltration of air, reducing heating and cooling costs • Can be completely covered with insulation.

## PRODUCT SPECIFICATIONS

**Lamp** Lamp ratings based on trim selected – see reverse.

**Socket** Floating medium base porcelain socket with nickel-plated copper screw shell • Shipped with socket cap to protect against paint overspray.

**Trims** Trim selection shown on reverse.

**Labels** UL/cUL listed for through-branch wiring, damp locations and IP  
 • Product thermally protected against improper use of lamps • Union made  
 • UL/CUL Listed • Trim No. V4012 is wet location approved for covered ceiling applications • Trim V4034 is wet location approved for covered ceiling applications, **when used with outdoor rated lamps.**

**Testing** All reports are based on published industry procedures; field performance may differ from laboratory performance.

## INSTALLATION

**Bar Hangers** Telescoping bar hangers with captive nail allow for quick placement of housing anywhere within 24" O.C. joists • Can be installed in suspended ceiling grid using T-bar clip accessory • Bars scored in two locations for fast clean breaking allowing housing installation in tight applications • Edge-mounted for extra strength and captive to mounting frame • May be installed either perpendicular or parallel to junction box • Locking set screw locks fixture in position • Alternate mounting holes included.

**Junction Box** Pre-wired junction box provided with (6) ½" and (1) ¾" knockouts, (4) Non-metallic sheathed cable connectors and ground wire, UL/cUL Listed for through-branch wiring, maximum 6 No. 12 AWG 90° C branch circuit conductors (3 in, 3 out) • Junction box provided with removable access plates • Knockouts equipped with pryout slots.

**Mounting Frame** 22-gauge die-formed galvanized steel mounting frame • 8⅝" L x 6" W, (excluding bar hangers) • Rough-in section (junction box, mounting frame, housing and bar hangers) fully assembled for ease of installation.

**Housing** Air-Loc IC housing, .032" aluminum • Inner housing is vertically adjustable to accommodate up to a 1¼" ceiling thickness.



**Warranty** 1-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at: [www.acuitybrands.com/support/warranty/terms-and-conditions](http://www.acuitybrands.com/support/warranty/terms-and-conditions)

**Note:** Actual performance may differ as a result of end-user environment and application.  
 Specifications subject to change without notice.

## PRODUCT CODES

Catalog No.	Input Voltage	Lamp Rating (max.)
V4IC W	120V	R16/R20/PAR16/PAR20 (See reverse for max. trim rating)

## DIMENSIONS



4 1/2" CEILING CUTOUT

## ACCESSORIES

Catalog No.	Description
G2405	T-Bar Clips (Set of 4)






To order, specify catalog number

# 4" IC NEW CONSTRUCTION HOUSING

## INCANDESCENT LAMPS

### V4IC W

#### TRIMS/LAMPS

	<b>Cat. No.</b>	<b>Description</b>	<b>Max. Lamp Rating</b>
	<b>V4034 WWH◆◆</b> <b>V4034 BWH◆◆</b>	White Baffle Full Black Baffle	50W PAR20, 30W R20
	<b>V4010 WH</b>	White Gimbal Ring	50W PAR20
	<b>V4018 WH</b>	White Eyeball	60W PAR16, 40W R16
	<b>V4012 WH◆</b>	Stippled Opal Lens Shower with Reflector	35W PAR20, 30W R20
	<b>V4040 WH</b>	White MR16 Gimbal Ring	35W MR16 GU10 Base (requires GU10-WHIP)

Trim Size: 5" O.D.

Trim Finish: WH - White.

Note: In Canada when insulation is present, Type IC fixtures must be used.

◆ UL/cUL Listed for use in wet location.

◆◆ UL/cUL Listed for use in wet location with outdoor rated lamp.

**AIR-LOC** Vulite IC housings meet IECC Energy Code requirements per ASTM E283.  
Air-Loc® rated trims are pre-gasketed for minimum air leakage with IC housings.

Vulite®

# 4" IC NEW CONSTRUCTION HOUSING

INCANDESCENT LAMPS

V4IC W

Project: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Location: \_\_\_\_\_

Contact/Phone: \_\_\_\_\_

## PRODUCT DESCRIPTION

IC Air-Loc® Housing with all 4" trims complies with IECC, Washington State and other state Energy Codes • Double wall construction • Energy efficient, sealed inner housing does not require separate ALG gasket • Air-Loc housing stops infiltration and exfiltration of air, reducing heating and cooling costs • Can be completely covered with insulation.

## PRODUCT SPECIFICATIONS

**Lamp** Lamp ratings based on trim selected – see reverse.

**Socket** Floating medium base porcelain socket with nickel-plated copper screw shell • Shipped with socket cap to protect against paint overspray.

**Trims** Trim selection shown on reverse.

**Labels** UL/cUL listed for through-branch wiring, damp locations and IP  
 • Product thermally protected against improper use of lamps • Union made  
 • UL/CUL Listed • Trim No. V4012 is wet location approved for covered ceiling applications • Trim V4034 is wet location approved for covered ceiling applications, **when used with outdoor rated lamps.**

**Testing** All reports are based on published industry procedures; field performance may differ from laboratory performance.

## INSTALLATION

**Bar Hangers** Telescoping bar hangers with captive nail allow for quick placement of housing anywhere within 24" O.C. joists • Can be installed in suspended ceiling grid using T-bar clip accessory • Bars scored in two locations for fast clean breaking allowing housing installation in tight applications • Edge-mounted for extra strength and captive to mounting frame • May be installed either perpendicular or parallel to junction box • Locking set screw locks fixture in position • Alternate mounting holes included.

**Junction Box** Pre-wired junction box provided with (6) ½" and (1) ¾" knockouts, (4) Non-metallic sheathed cable connectors and ground wire, UL/cUL Listed for through-branch wiring, maximum 6 No. 12 AWG 90° C branch circuit conductors (3 in, 3 out) • Junction box provided with removable access plates • Knockouts equipped with pryout slots.

**Mounting Frame** 22-gauge die-formed galvanized steel mounting frame • 8½" L x 6" W, (excluding bar hangers) • Rough-in section (junction box, mounting frame, housing and bar hangers) fully assembled for ease of installation.

**Housing** Air-Loc IC housing, .032" aluminum • Inner housing is vertically adjustable to accommodate up to a 1¼" ceiling thickness.



**Warranty** 1-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at: [www.acuitybrands.com/support/warranty/terms-and-conditions](http://www.acuitybrands.com/support/warranty/terms-and-conditions)

**Note:** Actual performance may differ as a result of end-user environment and application.  
 Specifications subject to change without notice.

## PRODUCT CODES

Catalog No.	Input Voltage	Lamp Rating (max.)
V4IC W	120V	R16/R20/PAR16/PAR20 (See reverse for max. trim rating)

## DIMENSIONS



4 1/2" CEILING CUTOUT

## ACCESSORIES

Catalog No.	Description
G2405	T-Bar Clips (Set of 4)






To order, specify catalog number

# 4" IC NEW CONSTRUCTION HOUSING

## INCANDESCENT LAMPS

### V4IC W

#### TRIMS/LAMPS

	<b>Cat. No.</b>	<b>Description</b>	<b>Max. Lamp Rating</b>
	<b>V4034 WWH◆◆</b> <b>V4034 BWH◆◆</b>	White Baffle Full Black Baffle	50W PAR20, 30W R20
	<b>V4010 WH</b>	White Gimbal Ring	50W PAR20
	<b>V4018 WH</b>	White Eyeball	60W PAR16, 40W R16
	<b>V4012 WH◆</b>	Stippled Opal Lens Shower with Reflector	35W PAR20, 30W R20
	<b>V4040 WH</b>	White MR16 Gimbal Ring	35W MR16 GU10 Base (requires GU10-WHIP)

Trim Size: 5" O.D.

Trim Finish: WH - White.

Note: In Canada when insulation is present, Type IC fixtures must be used.

◆ UL/cUL Listed for use in wet location.

◆◆ UL/cUL Listed for use in wet location with outdoor rated lamp.

**AIR-LOC** Vulite IC housings meet IECC Energy Code requirements per ASTM E283.  
Air-Loc® rated trims are pre-gasketed for minimum air leakage with IC housings.