

# CONNECTORS

## Mechanical Connectors

### Aluminum Service Wedge Clamps W Series



#### SPECIFICATIONS

- UL486A Listed for Wire Connector.
- Temperature Rating: 90 °C
- Voltage: 600V max.

#### FEATURES

- For dead-ending self-supporting drop wire.
- Saves conductor – drop wire may be cut to exact length.
- Can be attached to bare neutral in any point in the span.
- Adjustment in drop wire sag are easily made.
- Grips ACSR, AAAC or aluminum conductor.
- Catalog number with “FC” suffix have a Flexible bail.



| CAT. NO. | FIG. NO. | ACSR    | WIRE RANGE      |         | LENGTH (L) | WIDTH (W) | STD. CTN. QTY. |
|----------|----------|---------|-----------------|---------|------------|-----------|----------------|
|          |          |         | ALUMINUM        | AAAC    |            |           |                |
| W62-1    | 1        | 2-6     | 1 STR-6 SOL     | 2-6     | 12.000     | 2.375     | 12             |
| W62-1FC  | 2        | 2-6     | 1 STR-6 SOL     | 2-6     | 17.500     | FLEX      | 12             |
| W20-1    | 1        | 1/0-4   | 2/0 STR-2 SOL   | 1/0-4   | 12.500     | 2.375     | 8              |
| W20-1FC  | 2        | 1/0-4   | 2/0 STR-2 SOL   | 1/0-4   | 18.500     | FLEX      | 8              |
| W40-1    | 1        | 4/0-2/0 | 4/0 STR-2/0 SOL | 4/0-2/0 | 12.750     | 2.375     | 6              |
| W40-1FC  | 2        | 4/0-2/0 | 4/0 STR-2/0 SOL | 4/0-2/0 | 18.500     | FLEX      | 6              |

# CONNECTORS

## Mechanical Connectors

### Aluminum Service Wedge Clamps W Series



#### SPECIFICATIONS

- UL486A Listed for Wire Connector.
- Temperature Rating: 90 °C
- Voltage: 600V max.

#### FEATURES

- For dead-ending self-supporting drop wire.
- Saves conductor – drop wire may be cut to exact length.
- Can be attached to bare neutral in any point in the span.
- Adjustment in drop wire sag are easily made.
- Grips ACSR, AAAC or aluminum conductor.
- Catalog number with “FC” suffix have a Flexible bail.



| CAT. NO. | FIG. NO. | ACSR    | WIRE RANGE      |         | LENGTH (L) | WIDTH (W) | STD. CTN. QTY. |
|----------|----------|---------|-----------------|---------|------------|-----------|----------------|
|          |          |         | ALUMINUM        | AAAC    |            |           |                |
| W62-1    | 1        | 2-6     | 1 STR-6 SOL     | 2-6     | 12.000     | 2.375     | 12             |
| W62-1FC  | 2        | 2-6     | 1 STR-6 SOL     | 2-6     | 17.500     | FLEX      | 12             |
| W20-1    | 1        | 1/0-4   | 2/0 STR-2 SOL   | 1/0-4   | 12.500     | 2.375     | 8              |
| W20-1FC  | 2        | 1/0-4   | 2/0 STR-2 SOL   | 1/0-4   | 18.500     | FLEX      | 8              |
| W40-1    | 1        | 4/0-2/0 | 4/0 STR-2/0 SOL | 4/0-2/0 | 12.750     | 2.375     | 6              |
| W40-1FC  | 2        | 4/0-2/0 | 4/0 STR-2/0 SOL | 4/0-2/0 | 18.500     | FLEX      | 6              |