ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
Nacogdoches, TX 75964-0
Phone: 9365697941
Fax: 9365604685

WP1030MXD 2G RCP COVER

INTERMATIC INC.

Catalog Number	WP1030MXD
Manufacturer	INTERMATIC INC.
Description	Weatherproof Outlet Cover, 2 Gang, 6-3/8 in (L) x 5-5/8 in (W) x 3-1/8 in (H), Horizontal Mount/Vertical Mount, Rectangular, Die-Cast Aluminum, Gray
Weight per unit	1.4 (lbs/each)
Product Category	Wall Plates & Covers

Features

Cable Size	(2) 14 Gauge, (2) 12 Gauge
Knockouts	true
Warranty	1
Insulation	True
Number Of Outlet	2

Material, Color, and Finish

Color	Gray

Dimensions and Weight

Depth	3.125
Width	5.75

Descriptions

Construction	Heavy-Duty Die-Cast Aluminum
Description	2G RCP COVER
Long Description	Extra-Duty Die-Cast In-Use Weatherproof Cover, Double-Gang, Vrt, 3.125" Gray
Product Type	Extra-Duty Die-Cast In-Use Weatherproof Cover, Double-Gang,
Special Features	Features: Heavy-Duty Die-Cast Aluminum Construction Ensures Long-Lasting Durability, Reinforced Hinge Pin - Designed to Exceed 40lb Hinge Hang/Stress Test, Impact Rated 12 Lb Impact Test to Ensure Cover Remains In-Tact, Lockable Hasp All Models Accept Up To 0.25" Dia Shank, Meets Requirements For Cold Impact Testing -60øF (-51øC)
Extra Long Description	INT WP1030MXD Extra-Duty Die-Cast I

Manufacturer Information

Brand	Intermatic
GTIN	00078275130142
UPC	683341

Taxonomies, Classifications, and Categories

Category Description	WEATHERPROOF BOXES & COVERS
Type	Weatherproof Receptacle Cover

2310 N. Stallings Dr.
Nacogdoches, TX 75964-0
Phone: 9365697941
Fax: 9365604685

Packaging

Carton	1
Package	10
Weight Per Each	1.4 (lbs/each)

Uses, Certifications, and Standards

Application	Residential, Industrial, Sports Fields, Commercial, Agricultural, Signage
Mounting	VERTICAL
Standard	2014 NEC Article 406.9(B)(1), NEMA 3R, UL Listed, CSA, CEC Rule 26-702

Weather Proof Cover - Extra-Duty Die-Cast In-Use Weatherproof Cover, Double-Gang, Vrt, 3.125" Gray

Item WP1030MXD



PRODUCT DESCRIPTION

Die-Cast In-Use Aluminum Weatherproof Covers are extra-duty rated and easy to install. Heavy-duty die-cast aluminum construction ensures long-lasting durability. Covers come with a gasket, mounting screws, base, cover assembly and inserts to meet the needs of a variety of applications.

FEATURES

- Complies with 2020 NEC Article 406.9 (B)(1) for wet locations and extra-duty applications
- CEC Article 26-702 Compliant
- UL Certified for Type 3R outdoor enclosures
- Meets requirements for cold impact testing: -60° F (-51° C)
- Heavy-duty die-cast aluminum cover and mounting base with UV stabilized polycarbonate inserts
- 1/8" (3 mm) thick, neoprene gasket with slits for mounting screws
- Lockable hasp: All models accept up to 1/4" (6 mm) dia shank
- Impact rated: 12 lbf. impact test to ensure cover remains intact
- Reinforced hinge pin designed to exceed 40 lbf. hinge hang/stress test
- Warranty: 1-year limited
- Six inserts provided with all models that allow each model to meet multiple installations (up to 70 configurations)
- Max cord size: #12 AWG or smaller

APPLICATIONS

- Engine Block Heaters
- Receptacle Protection
- Walk-in Refrigeration Cooler/Freezer

TECHNICAL DATA

General	
Model Number	WP1030MXD
Description	Extra-Duty Die-Cast In-Use Weatherproof Cover, Double-Gang, Vrt, 3.125" Gray
UPC Code	078275130142
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited

Mechanical Specifications	
Number of Included Inserts	6
Insert Types Included	WP217
Hinge Direction	Vertical
Is Extra-Duty Rated	Yes

Dimensions	
Product Dimensions (H x W x D) in	6 3/8 x 5 5/8 x 3 1/8 in
Accepted Cord Size Max	2x12 AWG
Box Type	Double

Material Specifications	
Color	Gray

Weatherproof Cover Material	Die-Cast Aluminum

Packaging	
Shipping Weight (lbs)	1.35
Unit Carton Dimensions (H x W x L) in	3.25 x 5.75 x 6.312 in

Standards and Certifications	
UL Certification	cULus
CSA Certification	cCSAus
California Proposition 65	None

ACCESSORIES



WP217
Double-Gang Inserts (6)

Technical specifications and other information are subject to change without notice. Images can vary from original.