


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





WP3450BK Cat 5E RJ45 T568 A/B Conn BK (M20) Pass & Seymour/Legrand

Catalog Number	WP3450BK
Manufacturer	Pass & Seymour/Legrand
Description	The Vertical Design Of This High-Quality Insert Makes Punchdown Termination Easy. This Insert Is For Use In All Keystone Wall Plates and Is Available In Multiple Colors, As Well As Convenient Contractor Packs. It Ensures Category 6 Performance Standard Compliance and Includes Rear Retention Caps For Secure Wire Termination.
Weight per unit	0.0391 (lbs/each)
Product Category	Outlets, Jacks, & Plates
Features	
connection	RJ45 Female
Current Rating	1.5 (@ 20 degrees C)
Material, Color, and Finish	
Color	Black
Contact Material	Phosphor bronze alloy with 50 µin gold-plating over 100 µin nickel
Finish	Molded plastic chemically etched with diamond core finish
Dimensions and Weight Size	0.67 x 076 x 1.18 (17.02 x 19.30 x 29.97)
Descriptions	
Description	CAT 5E RJ45 T568 A/B CONN BK (M20)
extra long description	OnQ WP3450BK CAT 5E RJ45 T568 A/B C
Long Description	The vertical design of this high-quality insert makes punchdown termination easy. This insert is for use in all Keystone wall plates and is available in multiple colors, as well as convenient contractor packs. It ensures Category 6 performance standard compliance and includes rear retention caps for secure wire termination.
Product Type	Cat 5E RJ45 T568 A/B CNCTR BK (M20)
Special Features	Keyed, Cat 5e, RJ45, Keystone connector
Manufacturer Information	
Brand	Legrand On-Q
GTIN	00804428024897
Manufacturers Part Number	WP3450-BK
UPC	804428024897



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories	
Category Description	Datacom Wiring Devices and Accessories
Туре	Keyed RJ45 Female Cat 5e Keystone Insert
Packaging	
Carton	20
Package	120
Weight Per each	0.0391
Uses, Certifications, and Standard	s
Application	Residential
environmental conditions	0 to 93 (relative humidity, non-condensing)
Mounting	Keystone opening
standard	CSA, cULus, RoHS, ANSI/UL 1863, Flame-Retardant Plastic UL

94V-0