ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

WP3460BR Cat 6 RJ45 T568 A/B Conn BR (M20)
Pass & Seymour/Legrand

Catalog Number	WP3460BR
Manufacturer	Pass & Seymour/Legrand
Description	This High-Quality Cat 6 RJ45 Keystone Connector In Brown Is Perfect For Use In All Keystone Wall Plates. The Standard Rca Front Jack Connects to CAT5, CAT5E, or CAT6 Cables Terminated With RJ-45 Plugs. The Vertical Design Makes Punchdown Termination Easy, While Rear Retention Caps Ensure Secure Wire Connections.
Weight per unit	0.0369 (lbs/each)
Product Category	Fiber-Optic Connectors

Features

cutout	Cat6 RJ45 Punchdown
Material	High Impact Flame Retardant Plastic
orientation	Vertical

Material, Color, and Finish

Color	Brown

Dimensions and Weight

Size	0.87?x0.67?x1.29?

Descriptions

Description	CAT 6 RJ45 T568 A/B CONN BR (M20)
extra long description	OnQ WP3460BR CAT 6 RJ45 T568 A/B CN
Long Description	This high-quality Cat 6 RJ45 Keystone Connector in brown is perfect for use in all Keystone Wall Plates. The standard RCA front jack connects to Cat5, Cat5e, or Cat6 cables terminated with RJ-45 plugs. The vertical design makes punchdown termination easy, while rear retention caps ensure secure wire connections.
Product Type	Cat 6 RJ45 T568 A/B CNCTR BR (M20)
Special Features	Creates an Ethernet port. Connects to Cat5, Cat5e, or Cat6 cables terminated with RJ-45 plugs. Rear retention caps ensure secure wire termination. Vertical design for easy punchdown termination. T568 and T568B wiring labels included. Meets Category 6 desc

Manufacturer Information

Brand	ON-Q
GTIN	00804428024408
Manufacturers Part Number	WP3460-BR
UPC	804428024408

Taxonomies, Classifications, and Categories

Category Description	Datacom Wiring Devices and Accessories
Type	Keystone Insert

Packaging

Carton	20
Package	120
Weight Per each	0.0369

Uses, Certifications, and Standards

Application	Residential
Mounting	Wallplate or Strap
standard	ANSI/UL 1863, CAN/CSA-C22.2 No. 182.4-1990