ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
700 Industry Way Suite 10
75078-0000, TX Prosper
Phone: 469-899-3981
Fax: 469-899-3982



WR1010 1/0 to 1/0 H Tap

Abb Installation Products, Inc

Catalog Number	WR1010
Manufacturer	Abb Installation Products, Inc
Description	Aluminum Wide Range H-Type Compression Connector Main: 1/0-4 Acsr, 2/0-4 STR., 1- 2 Sol., Tap: 1/0-4 Acsr, 2/0-4 STR., 1-2 Sol., Die: 0
Weight per unit	0.0850 (lbs/each)
Product Category	Pole Line & Distribution Hardw

Features

connection	Compression
insulation	None
Number of Conductors	2
Wire Size	Main: 1/0 to #4 ACSR or 2/0 to #4 STR or #1 to #2 SOL AWG , Tap: 1/0 to #4 ACSR or 2/0 to #4 STR or #1 to #2 SOL AWG

Material, Color, and Finish

Housing Material	Aluminum

Dimensions and Weight

Size	Length 1-3/4 inch

Descriptions

Description	1/0 TO 1/0 H TAP
extra long description	TB WR1010 AL HTYPE COMP CONN 1/0-4A
Long Description	Aluminum Wide Range H-Type Compression Connector Main: 1/0-4 ACSR, 2/0-4 Str., 1- 2 Sol., Tap: 1/0-4 ACSR, 2/0-4 Str., 1-2 Sol., Die: 0
Product Type	Al Htype Comp Conn 1/0-4ASCR 2/0-4
Special Features	Made of 1350 Aluminum Alloy for high strength and high conductivity. Standard Compression tools and dies install all sizes - no special tools needed. Field-proven ribbed design enables excellent connector/conductor contact without distorting the conductor's shape. Fold-in tabs provide tab interlock as tool closes. Prefilled with oxide inhibitor held captive in the rib/connection area

Manufacturer Information

Brand	Blackburn Mechanical
GTIN	00783786107452
Manufacturers Part Number	WR1010
UPC	783786107452

ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
700 Industry Way Suite 10
75078-0000, TX Prosper
Phone: 469-899-3981
Fax: 469-899-3982

Taxonomies, Classifications, and Categories

Category Description	T&B C TAP LUGS
Type	H-Type Compression Tap Connector

Packaging

Carton	25
Package	250
Weight Per each	0.085

Uses, Certifications, and Standards

Application	For Combinations of Aluminum to Aluminum and Aluminum to Copper Conductors
environmental conditions	All Seasons / Conditions
Mounting	None
standard	RUS Accepted. Complies with ANSI C119.4 Specifications