

BUSHINGS

Sali Insulating Bushings Superior ADALET Laminated Insulation



TYPE PET



TYPE PEM

FEATURES

- Sali bushings are machined from paper laminated phenolic material and comply with NEMA-X phenolic material specifications.
- 11,000 psi tensile
- 17,000 flexural
- 450v/mil dielectric
- Heat resistance - 150° C, continuous
- Moisture absorption - 1/2 of 1%
- Listed by Underwriters Laboratories for your quality assurance.
- Sali bushings have been repeatedly proved in a wide variety of applications over a 25 year period.

Fittings & Accessories

TYPE PET-FEMALE-SET SCREW THREADLESS

Catalog #	Conduit Size (in.)	Nominal Dimensions (in.)				Std. Package	
		I.D.1	O.D.	Height	I.D.2	Qty.	Weight (lbs. per 100)
PET-2	1/2	5/8	1 1/8	5/8	7/8	50	1 1/2
PET-3	3/4	13/16	1 5/16	5/8	1 1/16	50	2
PET-4	1	1	1 5/8	25/32	1 11/32	50	3 1/2
PET-5	1 1/4	1 3/8	2	25/32	1 11/16	25	4 1/2
PET-6	1 1/2	1 5/8	2 1/4	25/32	1-15/16	25	5 1/2
PET-8	2	2	2 3/4	25/32	2 13/32	10	7 1/2
PET-10	2 1/2	2 7/16	3 1/4	1	2 29/32	5	12
PET-12	3	3	3 7/8	1 1/16	3 17/32	5	14
PET-14	3 1/2	3 1/2	4 3/8	1 1/16	4 1/32	5	17
PET-16	4	4	5	1 1/16	4 17/32	2	25

For threadless rigid conduit on all free conduit terminals such as terminating behind or within switchboards, switchgear, etc.

TYPE PEM

Catalog #	Conduit Size (in.)	Nominal Dimensions (in.)			Std. Package	
		I.D.	O.D.	Height	Qty.	Weight (lbs. per 100)
PEM-2	1/2	5/8	1 1/8	5/8	50	1
PEM-3	3/4	13/16	1 5/16	5/8	50	1 1/2
PEM-4	1	1	1 5/8	25/32	50	2 1/2
PEM-5	1 1/4	1 3/8	2	25/32	25	3
PEM-6	1 1/2	1 5/8	2 1/4	25/32	25	4
PEM-8	2	2	2 3/4	25/32	10	6
PEM-10	2 1/2	2 7/16	3 1/4	1 1/16	5	10
PEM-12	3	3	3 7/8	1 1/16	5	14
PEM-14	3 1/2	3 1/2	4 3/8	1 1/16	5	16 1/2
PEM-16	4	4	5	1 1/16	2	21

A high strength resilient male bushing recommended to protect wires passing through steel cabinet walls, metal partitions and similar applications. For additional strength it is recommended this bushing be secured with type PE deep threaded female bushing.

Certifications

Type PET & SPE: UL Listed
Type PEM: UL Listed

