

# Guarded Pilot Lights for Group B Applications



**XL Long Series  
(Panel Mount)**



**XLS Short Series  
(Surface Mount)**



**Replacement Cap**

**Class I, Groups B, C & D  
Class II, Groups E, F & G  
NEMA 3, 4, 7 & 9**

## FEATURES

- Explosionproof pilot lights are suitable for panel or surface mount applications.
- Sealed construction and can be relamped from the front by removal of lens cap.
- Made with 3/4" NPSM threads.
- 8" flexible leads, other lengths on special order, or screw terminal (suffix T).
- All lens caps are black anodized aluminum finish.
- **Maximum installation thickness:** 1 13/16" on Long Series, 5/8" on Short Series.
- **Standard Series**-Equipped with candelabra base receptacles and 6 watt 120 volt 6S6 Clear 1500 hr. avg. lamps. Also available with 6, 12, 24, 30, 50, 75 and 135 volt lamps. Specify voltage desired.
- **Slide Base Series**-Equipped with slide base receptacles and 120 volt 5000 hr. avg. lamps with slide base. Also available with 6, 12, 24, 48 and 60 volt lamps. Specify voltage desired.

## STANDARD SERIES

| Panel Mount Cat # | Surface Mount Cat # | Description | Weight (lbs.) |
|-------------------|---------------------|-------------|---------------|
| XLA-GH            | XLSA-GH             | Amber Lens  | 1/2           |
| XLB-GH            | XLSB-GH             | Blue Lens   | 1/2           |
| XLC-GH            | XLSC-GH             | Clear Lens  | 1/2           |
| XLG-GH            | XLSG-GH             | Green Lens  | 1/2           |
| XLR-GH            | XLSR-GH             | Red Lens    | 1/2           |
| XLW-GH            | XLSW-GH             | White Lens  | 1/2           |

## SLIDE BASE SERIES

| Panel Mount Cat # | Surface Mount Cat # | Description | Weight (lbs.) |
|-------------------|---------------------|-------------|---------------|
| XLAS-GH           | XLSAS-GH            | Amber Lens  | 1/2           |
| XLBS-GH           | XLSBS-GH            | Blue Lens   | 1/2           |
| XLCS-GH           | XLSCS-GH            | Clear Lens  | 1/2           |
| XLGS-GH           | XLSGS-GH            | Green Lens  | 1/2           |
| XLRS-GH           | XLSRS-GH            | Red Lens    | 1/2           |
| XLWS-GH           | XLSWS-GH            | White Lens  | 1/2           |

\*Add suffix T to P/N for screw terminal (Example: XLAST-GH)

## REPLACEMENT CAP

| Cat #   | Description | Weight (lbs.) |
|---------|-------------|---------------|
| XLA-GCH | Amber Lens  | 1/8           |
| XLB-GCH | Blue Lens   | 1/8           |
| XLC-GCH | Clear Lens  | 1/8           |
| XLG-GCH | Green Lens  | 1/8           |
| XLR-GCH | Red Lens    | 1/8           |
| XLW-GCH | White Lens  | 1/8           |

# Guarded Pilot Lights for Group B Applications



**XL Long Series  
(Panel Mount)**



**XLS Short Series  
(Surface Mount)**



**Replacement Cap**

**Class I, Groups B, C & D  
Class II, Groups E, F & G  
NEMA 3, 4, 7 & 9**

## FEATURES

- Explosionproof pilot lights are suitable for panel or surface mount applications.
- Sealed construction and can be relamped from the front by removal of lens cap.
- Made with 3/4" NPSM threads.
- 8" flexible leads, other lengths on special order, or screw terminal (suffix T).
- All lens caps are black anodized aluminum finish.
- **Maximum installation thickness:** 1 13/16" on Long Series, 5/8" on Short Series.
- **Standard Series**-Equipped with candelabra base receptacles and 6 watt 120 volt 6S6 Clear 1500 hr. avg. lamps. Also available with 6, 12, 24, 30, 50, 75 and 135 volt lamps. Specify voltage desired.
- **Slide Base Series**-Equipped with slide base receptacles and 120 volt 5000 hr. avg. lamps with slide base. Also available with 6, 12, 24, 48 and 60 volt lamps. Specify voltage desired.

## STANDARD SERIES

| Panel Mount Cat # | Surface Mount Cat # | Description | Weight (lbs.) |
|-------------------|---------------------|-------------|---------------|
| XLA-GH            | XLSA-GH             | Amber Lens  | 1/2           |
| XLB-GH            | XLSB-GH             | Blue Lens   | 1/2           |
| XLC-GH            | XLSC-GH             | Clear Lens  | 1/2           |
| XLG-GH            | XLSG-GH             | Green Lens  | 1/2           |
| XLR-GH            | XLSR-GH             | Red Lens    | 1/2           |
| XLW-GH            | XLSW-GH             | White Lens  | 1/2           |

## SLIDE BASE SERIES

| Panel Mount Cat # | Surface Mount Cat # | Description | Weight (lbs.) |
|-------------------|---------------------|-------------|---------------|
| XLAS-GH           | XLSAS-GH            | Amber Lens  | 1/2           |
| XLBS-GH           | XLSBS-GH            | Blue Lens   | 1/2           |
| XLCS-GH           | XLSCS-GH            | Clear Lens  | 1/2           |
| XLGS-GH           | XLSGS-GH            | Green Lens  | 1/2           |
| XLRS-GH           | XLSRS-GH            | Red Lens    | 1/2           |
| XLWS-GH           | XLSWS-GH            | White Lens  | 1/2           |

\*Add suffix T to P/N for screw terminal (Example: XLAST-GH)

## REPLACEMENT CAP

| Cat #   | Description | Weight (lbs.) |
|---------|-------------|---------------|
| XLA-GCH | Amber Lens  | 1/8           |
| XLB-GCH | Blue Lens   | 1/8           |
| XLC-GCH | Clear Lens  | 1/8           |
| XLG-GCH | Green Lens  | 1/8           |
| XLR-GCH | Red Lens    | 1/8           |
| XLW-GCH | White Lens  | 1/8           |