# Specifications



### Photo is representative





## Eaton XTCE065DS1A

Eaton XT IEC contactor, 65A, Side-mounted, 110 Vac 50 Hz, 120 Vac 60 Hz, 1NO-1NC, 65A, Frame D, 55 mm, 50-60 Hz, 5, 10, 15/ 20, 25, 50, 60 hp(1/3PH @115, 200, 230/200, 230, 460, 575 V), Three-pole, Screw terminals, FVNR

General specifications		
PRODUCT NAME	Eaton XT IEC contactor	
CATALOG NUMBER	XTCE065DS1A	
UPC	786685365121	
PRODUCT LENGTH/DEPTH	1 in	
PRODUCT HEIGHT	1 in	
PRODUCT WIDTH	1 in	
PRODUCT WEIGHT	1 lb	
WARRANTY	Eaton Selling Policy 25- 000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.	
CERTIFICATIONS	CSA Certified UL Listed EN 60947 IEC 60947	



Product specifications		
AMPERAGE RATING	65A	
HP RATING - MAX	5, 10, 15/ 20, 25, 50, 60 hp (1/3PH @115,200,230/200,230,460,575 V)	
NUMBER OF POLES	Three-pole	
ТҮРЕ	Full voltage non-reversing contactor	
FREQUENCY RATING	50-60 Hz	
FRAME SIZE	55 mm	
TERMINALS	Screw terminals	
COIL	110-120 Vac, 50/60 Hz	
COIL VOLTAGE	110-120 Vac, 50/60 Hz	
CONTACT CONFIGURATION	1 NO, 1 NC	
CONTINUOUS AMPERE RATING	65 A	
SERIES	XT IEC	
OPERATION	Non-reversing	

Resources	
CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTCE065DS1A
WARRANTY GUIDES	Selling Policy 25-000 - Distribution and Control Products and Services

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



**Eaton Corporation plc** Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Follow us on social media to get the latest product and support information.











# Specifications



### Photo is representative





## Eaton XTCE065DS1A

Eaton XT IEC contactor, 65A, Side-mounted, 110 Vac 50 Hz, 120 Vac 60 Hz, 1NO-1NC, 65A, Frame D, 55 mm, 50-60 Hz, 5, 10, 15/ 20, 25, 50, 60 hp(1/3PH @115, 200, 230/200, 230, 460, 575 V), Three-pole, Screw terminals, FVNR

General specifications		
PRODUCT NAME	Eaton XT IEC contactor	
CATALOG NUMBER	XTCE065DS1A	
UPC	786685365121	
PRODUCT LENGTH/DEPTH	1 in	
PRODUCT HEIGHT	1 in	
PRODUCT WIDTH	1 in	
PRODUCT WEIGHT	1 lb	
WARRANTY	Eaton Selling Policy 25- 000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.	
CERTIFICATIONS	CSA Certified UL Listed EN 60947 IEC 60947	



Product specifications		
AMPERAGE RATING	65A	
HP RATING - MAX	5, 10, 15/ 20, 25, 50, 60 hp (1/3PH @115,200,230/200,230,460,575 V)	
NUMBER OF POLES	Three-pole	
ТҮРЕ	Full voltage non-reversing contactor	
FREQUENCY RATING	50-60 Hz	
FRAME SIZE	55 mm	
TERMINALS	Screw terminals	
COIL	110-120 Vac, 50/60 Hz	
COIL VOLTAGE	110-120 Vac, 50/60 Hz	
CONTACT CONFIGURATION	1 NO, 1 NC	
CONTINUOUS AMPERE RATING	65 A	
SERIES	XT IEC	
OPERATION	Non-reversing	

Resources	
CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTCE065DS1A
WARRANTY GUIDES	Selling Policy 25-000 - Distribution and Control Products and Services

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



**Eaton Corporation plc** Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Follow us on social media to get the latest product and support information.









