

# Specifications



## Eaton XTCEXFAC04

Eaton Contactor Accessory Auxiliary Contact, Four-pole, Screw terminals, 4NC contact configuration, 16A conventional thermal rating, 6A at 220/230/240V, 3A at 380/400/415V, 1.5A at 500V rated operational voltage, Front mounting,

### General specifications

<b>PRODUCT NAME</b>	Eaton motor control auxiliary contact
<b>CATALOG NUMBER</b>	XTCEXFAC04
<b>UPC</b>	782116354559
<b>PRODUCT LENGTH/DEPTH</b>	1.5 in
<b>PRODUCT HEIGHT</b>	1.3 in
<b>PRODUCT WIDTH</b>	1.5 in
<b>PRODUCT WEIGHT</b>	0.12 lb
<b>COMPLIANCES</b>	CCC Marked CE Marked ATEX Compliant
<b>CERTIFICATIONS</b>	IEC 60947 EN 60947 UL Listed CSA Certified
<b>CATALOG NOTES</b>	Interlocked opposing contacts, to IEC/EN 60947-5-1 Annex L (positively driven), within the auxiliary contact modules (not NOE and NCL contacts) and between the auxiliary contacts and built-in contacts of the XTRE control relays.



Powering Business Worldwide

## Product specifications

<b>USED WITH</b>	XTRE control relays
<b>NUMBER OF POLES</b>	Four-pole
<b>TYPE</b>	Contactor Accessory - Auxiliary Contact
<b>TERMINALS</b>	Screw
<b>CONTACT CONFIGURATION</b>	4 NC
<b>MOUNTING METHOD</b>	Front
<b>RATED OPERATIONAL CURRENT</b>	6A at 220/230/240V; 3A at 380/400/415V; 1.5A at 500V
<b>SPECIAL FEATURES</b>	Used with XTRE control relays
<b>CONVENTIONAL THERMAL CURRENT</b>	16A
<b>QUANTITY</b>	5

## Resources

### SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - XTCEXFAC04](#)

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

