Eaton XTCR009B21TD

Catalog Number: XTCR009B21TD

Eaton XT IEC contactor, 9A, 24 Vdc, 2NO-2NO, 9A, Frame B, 45 mm, 0.5, 1.5/ 3, 3, 5, 7.5 hp (1/3PH @115, 230/200, 230, 460, 575 V), Three-pole, Reversing, XT IEC series, Screw terminals, Full voltage reversing contactor

General specifications

Product Name Eaton XT IEC contactor

UPC

782116884896

Product Height 68 mm

Product Weight 0.28 kg

Compliances

CE Marked RoHS Compliant

Catalog Notes

Catalog Number XTCR009B21TD

Product Length/Depth 117 mm

Product Width 90 mm

Warranty

1 year

Certifications

CSA Certified EN 60947 UL Listed IEC 60947



Photo is representative

Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)



Product specifications

Amperage Rating

9A

HP rating - max

0.5, 1.5/ 3, 3, 5, 7.5 hp (1/3PH @115,230/200,230,460,575 V)

Number Of Poles

Three-pole

Туре

Full voltage reversing contactor

Frame size

45 mm

Terminals

Screw terminals

Coil voltage

24 Vdc

Contact configuration

2 NO, 2 NO

Continuous ampere rating

9 A

Series

XT IEC

Operation

Reversing



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

© 2025 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia

Resources

Specifications and datasheets

Eaton Specification Sheet - XTCR009B21TD

Eaton XTCR009B21TD

Catalog Number: XTCR009B21TD

Eaton XT IEC contactor, 9A, 24 Vdc, 2NO-2NO, 9A, Frame B, 45 mm, 0.5, 1.5/ 3, 3, 5, 7.5 hp (1/3PH @115, 230/200, 230, 460, 575 V), Three-pole, Reversing, XT IEC series, Screw terminals, Full voltage reversing contactor

General specifications

Product Name Eaton XT IEC contactor

UPC

782116884896

Product Height 68 mm

Product Weight 0.28 kg

Compliances

CE Marked RoHS Compliant

Catalog Notes

Catalog Number XTCR009B21TD

Product Length/Depth 117 mm

Product Width 90 mm

Warranty

1 year

Certifications

CSA Certified EN 60947 UL Listed IEC 60947



Photo is representative

Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)



Product specifications

Amperage Rating

9A

HP rating - max

0.5, 1.5/ 3, 3, 5, 7.5 hp (1/3PH @115,230/200,230,460,575 V)

Number Of Poles

Three-pole

Туре

Full voltage reversing contactor

Frame size

45 mm

Terminals

Screw terminals

Coil voltage

24 Vdc

Contact configuration

2 NO, 2 NO

Continuous ampere rating

9 A

Series

XT IEC

Operation

Reversing



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

© 2025 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia

Resources

Specifications and datasheets

Eaton Specification Sheet - XTCR009B21TD