

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



YGLR29C34 2-250 Ground Grid to 3/4 Ro Burndy LLC

Catalog Number	YGLR29C34
Manufacturer	Burndy LLC
Description	Copper Compression Connector, Ground Rod to Grid, 2 Awg (STR) to 250 Kcmil, 3/4" Ground Rod.
Weight per unit	0.9900 (lbs/each)
Product Category	Large Terminals & Connectors
eatures	
Die Index	997
Material	Copper
pallet quantity	1776
escriptions	
Description	2-250 GROUND GRID TO 3/4 RO
extra long description	BUR YGLR29C34 2-250 GRD GRID TO 3/4
Long Description	Copper Compression Connector, Ground Rod to Grid, 2 AWG (Str to 250 kcmil, 3/4" Ground Rod.
Product Type	Compression
Special Features	Features: Ground Grid Connector For A Wide Range Of Copper Cable To Ground Rod, Provides High Torque Strength On Ground Rod, UL467 Listed, Acceptable For Direct Burial In Earth And Concrete, Prefilled With PENETROX Compound And Strip Sealed, Ground Rod Size: 3/4 IN, Conductor Size (run - Mm): 35 -120 SQ-MM, Conductor Type: Run: Copperweld, Commercial Stranded Copper, Metric Stranded Cable, Conductor Size (run - Range): Copperweld: 91.65 - 248.8 KCMIL, Code: 2 AWG - 250 KCMIL, Tools, Die Set Catalog Number,
lanufacturer Information	
Brand	BURNDY
GTIN	00781810220825
Manufacturers Part Number	YGLR29C34
UPC	781810220825

Tax

Category Description	SERVICE ENTRANCE FITTINGS: Weatherheads & Grounding
	Fittings & Ground Rods
Туре	Taps

Packaging

ckaging	
Carton 1	
Package 6	
Weight Per each 0.99	

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Tax. 730-300-4

Uses, Certifications, and Standards

Application	For Direct Burial In Earth And Concrete
standard	UL467;IEEE 837;IEEE 837 2014 Qualified